


TI TDA4VM SMARC – Accelerated Computing

conga-STDA4




- SMARC Module based on TI TDA4VM AI application processor
- Heterogenous architecture with Arm® Cortex®-A72, DSP and accelerators for deep learning and AI
- Arm® Cortex®-R5F to offload real-time communication
- Highest reliability for harsh environment applications
- Industrial temperature range -40°C to +85°C



| | | | | | | |
|-------------------------------|---|-----------------------|-------------------------------|--|-------------------------------|--------------------------------|
| Form factor | SMARC Module Specification 2.2 | | | | | |
| SoC | TI TDA4VM Arm® Application and Networking Processors | | | | | |
| | Arm Cortex-A72 | ARM Cortex-R5F | DSP Cores | MMA | GPU | |
| | TDA4VM88 | 2x @ 2.0 GHz | 6x @ 1.0 GHz | 1x C7x up to 80 GFLOPs & 2x C66 up to 40 GFLOPs | Deep Learning up to 8 TOPS | 3D PowerVR Rogue 8XE GE8430 |
| DRAM | Up to 8 GB onboard LPDDR4 memory 4266 MT/s inline ECC 8 MB of on-chip L3 RAM with ECC and coherency 512KB on-chip SRAM in MAIN domain, protected by ECC | | | | | |
| Ethernet | 2x Gbit Ethernet with IEEE 1588 support | | | | | |
| I/O Interfaces | 1x dual-role USB 2.0 2x USB 2.0 2x USB 3.0 1x SDIO 3.0 2x PCIe 3.0 x1 + 1x PCIe 3.0 x2 or up to 3x PCIe 3.0 x1 2x I ² C 2x SPI 4x UART (2x with Handshake) 2x CAN FD 14x GPIO optional full industrial onboard u-blox WiFi/BT module | | | | | |
| Mass Storage | eMMC 5.1 up to 128 GB optional pseudo-SLC | | | | | |
| Sound | 2x I ² S | | | | | |
| Graphics | Integrated in SoC Graphics Accelerator 3D GPU PowerVR Rogue 8XE GE8430 up to 1x Ultra-HD or 4x Full-HD 30fps display resolution up to 4 concurrent displays VPU up to 4kp30 H.264/H.265 decode / 1080p60 H.264 encode OpenGL ES 3.1 OpenVX OpenCL | | | | | |
| Video Interfaces | 1x dual channel 24-bit LVDS 1x Display Port up to 4kp30 optional 1x MIPI-DSI 4-lane shared with LVDS 2x MIPI-CSI integrated Image Signal Processor (ISP) for camera on TDV4VM | | | | | |
| Features | Watchdog Timer Console Port high precision Real Time Clock | | | | | |
| AI & Deep Learning | Deep-learning Matrix Multiply Accelerator Accelerators (MMA) with up to 8 TOPS (8b) C7x floating point, vector DSP with up to 80 GFLOPs Vision Processing Accelerators (VPAC) with Image Signal Processor (ISP) and multiple vision assist accelerators Depth and Motion Processing Accelerators (DMPAC) | | | | | |
| Security | Customer programmable root key, up to RSA-4K or ECC-512 Crypto hardware accelerators, PKA with ECC, AES, SHA, RNG, DES and 3DES Secure boot with secure runtime support SHE, Encryption Engine AES-128/192/256, TRNG, SHA-1, SHA1 and SHA2-224/256/384/512, MD5 RSA-1024, 2048, 3072, 4096 and secure key storage | | | | | |
| Boot Loader | U-Boot boot loader | | | | | |
| Operating Systems | Linux | | | | | |
| Power Consumption | Typ. application 5-10W @ 5V | | | | | |
| Temperature Range | Operating Temperature Range: | | -40 to +85°C industrial grade | | | |
| | Storage Temperature Range: | | -40 to +85°C | | | |
| Humidity | Operating: | | 10% to 85% r. H. non cond. | | | |
| | Storage: | | 5% to 85% r. H. non cond. | | | |
| Size | 82 x 50 mm (3,23" x 1,97") | | | | | |

conga-STDA4 | Block Diagram



* Assembly Option

conga-STDA4 | Order Information

| Article | PN | Description |
|---|--------|---|
| conga-STDA4/i-TDA4VM-4G eMMC32 | 051510 | SMARC Module based on high-performance industrial TI TDA4VM Arm® Application processor. Features 2x ARM Cortex-A72 @ 2.0GHz + 6x ARM Cortex-R5F + 8 TOPS MMA (deep-learning matrix multiply accelerator), 4GB onboard LPDDR4 memory and 32GB onboard eMMC. Industrial grade temperature range from -40°C to +85°C. |
| conga-STDA4/i-TDA4VM-2G eMMC32 | 051511 | SMARC Module based on high-performance industrial TI TDA4VM Arm® Application processor. Features 2x ARM Cortex-A72 @ 2.0GHz + 6x ARM Cortex-R5F + 8 TOPS MMA (deep-learning matrix multiply accelerator), 2GB onboard LPDDR4 memory and 32GB onboard eMMC. Industrial grade temperature range from -40°C to +85°C. |
| conga-STDA4/i-TDA4VM-2G eMMC32 MAYA-W260 | 051520 | SMARC Module based on high-performance industrial TI TDA4VM Arm® Application processor. Features 2x ARM Cortex-A72 @ 2.0GHz + 6x ARM Cortex-R5F + 8 TOPS MMA (deep-learning matrix multiply accelerator), 2GB onboard LPDDR4 memory and 32GB onboard eMMC. Features u-blox Wifi/BT module MAYA-W260. Industrial grade temperature range from -40°C to 85°C. |
| conga-STDA4/CSP-B | 051550 | Passive cooling solution for SMARC Module conga-STDA4 based on TI TDA4VM Arm® processors. All standoffs are with 2.7 mm bore hole. |
| conga-STDA4/HSP-B | 051551 | Standard heatspreader for SMARC Module conga-STDA4 based on TI TDA4VM Arm® processors. All standoffs are with 2.7 mm bore hole. |
| SMARC/CSA Adapter | 050060 | Active cooling solution adapter for SMARC modules used in combination with module heat spreader. |
| conga-SEVAL | 007010 | Evaluation carrier board for SMARC modules. |
| conga-SMC1/SMARC-ARM | 020750 | 3.5" carrier board for congatec SMARC modules based on ARM architecture. |